

# WPF 10 M

BRINE | WATER HEAT PUMPS

PRODUCT-NO.: 185349

The modular WPF range is a brine/water heat pump system that is capable of delivering renewable energy to buildings on a much larger scale. The combination of up to six heat pumps means that the system can deliver a combined output of up to 100 kW. That makes it perfect for heating larger buildings or apartments for example. The system meters out its heating output via up to two controllers, making the system control very easy indeed. The modules can be matched, stage-by-stage, to your individual requirements, to deliver an energy supply solution for central heating which is tailor-made under ecological and economical aspects.



## The main features

10.02 kW heating output at B0/W35

---

Heating flow temperature up to 60 °C

---

Extremely quiet operation

---

Suitable for cascade control for a higher output requirements



Type	WPF 10 M	WPF 10 MS	WPF 13 M	WPF 16 M
Part no.	185349	222552	182135	220894
Output at B0/W35 (EN 14511)	10,02 kW	9,90 kW	12,98 kW	16,99 kW
Coefficient of performance at B0/W35 (EN 14511)	4,49	4,50	4,57	4,35

Technical data

Energy efficiency class, heat pump W35	A++	A++	A++	A++
Energy efficiency class, W55 heat pump	A+	A+	A++	A+
Energy efficiency class, composite system (heat pump + controller) W35	A+++	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A+	A++	A++	A+
Flow rate, heat source side	2,2 m <sup>3</sup> /h	2,2 m <sup>3</sup> /h	3,1 m <sup>3</sup> /h	3,8 m <sup>3</sup> /h
Sound power level (EN 12102)	51 dB(A)	51 dB(A)	51 dB(A)	51 dB(A)
Sound pressure level at a distance of 1 m	40 dB(A)	40 dB(A)	40 dB(A)	45 dB(A)
Rated compressor voltage	400 V	230 V	400 V	400 V
Height	960 mm	960 mm	960 mm	960 mm
Width	510 mm	510 mm	510 mm	510 mm
Depth	680 mm	640 mm	680 mm	680 mm
Weight	112 kg	120,5 kg	120 kg	125 kg



Type	<b>WPF 7 MS</b>
Part no.	222553
Output at B0/W35 (EN 14511)	7,80 kW
Coefficient of performance at B0/W35 (EN 14511)	4,40
<b>Technical data</b>	
Energy efficiency class, heat pump W35	A++
Energy efficiency class, W55 heat pump	A+
Energy efficiency class, composite system (heat pump + controller) W35	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A+
Flow rate, heat source side	1,9 m <sup>3</sup> /h
Sound power level (EN 12102)	47 dB(A)
Sound pressure level at a distance of 1 m	36 dB(A)
Rated compressor voltage	230 V
Height	971 mm
Width	510 mm
Depth	640 mm
Weight	107 kg

Short term (max. 30 min) HS temperature up to 40 °C permissible.

Have we sparked your interest? For further information visit  
[www.stiebel.co.nz](http://www.stiebel.co.nz) or call 09 486 2221

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.